



版本 Edition	变更内容 Description of the change




标配：A型圆头普通平键
A12X8X56(GB/T1096)

正样
2026.03.09
A



风扇电源PG11防水接头




电源PG36防水接头




电机技术参数 Motor parameters

额定电压 Rated voltage	380	V AC
额定功率 Rated power	7.1	kW
额定扭矩 Rated torque	40	N · m
额定电流 Rated current	13.3	Arms
峰值扭矩(850rpm) Peak torque	100	N · m
峰值电流(850rpm) Peak current	34.6	Arms
峰值扭矩(1700rpm) Peak torque	75	N · m
峰值电流(1700rpm) Peak current	30.5	Arms
峰值扭矩(2700rpm) Peak torque	43	N · m
峰值电流(2700rpm) Peak current	25.1	Arms
额定转速 Rated speed	1700	rpm
峰值转速 Maximum speed	2700	rpm
扭矩系数 Torque constant	3.05	N · m/Arms
反电势常数 Back EMF constant	199.9	V/krpm
线电阻 line resistance	1.58	Ω
线电感 line inductance	23.2	mH
转动惯量 Moment of inertia	52 ± 10%	kg · cm ²
轴向允许载荷 Axial allowable load	/	N
径向允许载荷 Radial allowable load	/	N
极对数 Number of pole pairs	4	对

引线定义 Wiring definition




Speed-torque characteristic curve



IP 防护等级 Ingress Protection Rating	IP54	
绝缘等级 Insulation class	F	
绝缘电阻 Insulation resistance	> 100MΩ DC500V	
电机重量 Motor weight	35.2	kg
工作温度 Operating temperature	-20℃~40℃	
工作湿度 Operating humidity	20%~80% (不结露 Non-dewfall)	
推荐安装海拔 Recommend installing altitude	< 1000m(1km 以上降额使用) (Derate for use above 1km)	

信号航插规格 Encoder connector

YD28J15Z




编码器规格 Connector specifications

23-bit
optical encoder

12-bit
Resolver encoder

引线定义 Wiring definition										
1	2	3	4	5	6	7	8	9		
PE (屏蔽)	SD+ (蓝)	SD- (黄)	+5V (红)	0V (黑)	BAT+ (棕)	BAT- (白)	KTY84-130+ (黄)	KTY84-130- (绿)		
PE (屏蔽)	Ref+ (红白)	Ref- (黄白)	Cos- (黑)	Cos+ (红)	Sin+ (黄)	Sin- (蓝)	KTY84-130+ (黄)	KTY84-130- (绿)		

SN	料号 P/N	整机型号 Model and Specification			编码器 Encoder			
	11101-01430	IMS20B-20M71C17C-4-R7F-A			12位旋变			
	11101-01431	IMS20B-20M71C17C-4-P9F-A			23位多圈光编			
				深圳市英威腾电气股份有限公司 Shenzhen INVT Electric Co., Ltd.				
A	新归档	/	26-2-9	名 称	电机外形图 Motor outline dimension drawing			
版 本	更改方式	更改人	日期					
设计	/			料 号	/	材 质	/	
校 核	/							
工 艺	/			图 号	/	投影标识		
审 核	/							
标准化	/			重 量	/	比 例	1 : 1	
批 准	/					第 1 页 共 1 页		